

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
22 January 2004 (22.01.2004)


PCT

(10) International Publication Number
WO 2004/008721 A1

- | | |
|---|--|
| <p>(51) International Patent Classification⁷: H04M 1/02,
1/725, H01R 12/18</p> <p>(21) International Application Number:
PCT/EP2003/005715</p> <p>(22) International Filing Date: 31 May 2003 (31.05.2003)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data:
02445096.7 12 July 2002 (12.07.2002) EP
02445141.1 22 October 2002 (22.10.2002) EP
60/426,114 14 November 2002 (14.11.2002) US</p> <p>(71) Applicant (for all designated States except US): SONY
ERICSSON MOBILE COMMUNICATIONS AB
[SE/SE]; S-221 88 LUND (SE).</p> <p>(72) Inventor; and</p> <p>(75) Inventor/Applicant (for US only): RYDGREN, Åke
[SE/SE]; Norrevång 16, S-247 34 Södra Sandby (SE).</p> | <p>(74) Agents: LINDBERG, Olle et al.; Albihns Malmö AB,
P.O. Box 4289, S-203 14 Malmö (SE).</p> <p>(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.</p> <p>(84) Designated States (regional): ARIPO utility model (GH), ARIPO patent (GH), ARIPO utility model (GM), ARIPO patent (GM), ARIPO utility model (KE), ARIPO patent (KE), ARIPO utility model (LS), ARIPO patent (LS), ARIPO utility model (MW), ARIPO patent (MW), ARIPO utility model (MZ), ARIPO patent (MZ), ARIPO utility model (SD), ARIPO patent (SD), ARIPO utility model (SL), ARIPO patent (SL), ARIPO utility model (SZ), ARIPO patent (SZ), ARIPO utility model (TZ), ARIPO</p> |
|---|--|

[Continued on next page]

- (54) Title:** RADIO COMMUNICATION TERMINAL WITH A DETACHABLE ACTIVE HOUSING AND RELATED CONNECTOR



- (57) **Abstract:** A radio communication terminal (1) comprising data processing means for controlling terminal functions, and attaching means (27) for releasable attachment of a housing (30) to the terminal, wherein said terminal comprises a multipath connector (17) connected to the data processing means, and wherein said multipath connector includes a terminal system connector, and a housing connector for communicative connection of an attached housing to the data processing means. The housing or cover also comprises functional means that are adapted to modify or to add a feature to the terminal. New functionalities can therefore be added to the terminal by replacing the housing or cover.

WO 2004/008721 A1



patent (TZ), ARIPO utility model (UG), ARIPO patent (UG), ARIPO utility model (ZM), ARIPO patent (ZM), ARIPO utility model (ZW), ARIPO patent (ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*

- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations*
- *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

5/2004

ACTIVE HOUSING FOR COMMUNICATION TERMINALS

Field of the invention

The present invention relates generally to radio communication terminals having a detachable housing or cover, and to such detachable housings or covers. In particular, the invention relates to releasably attachable active housings devised to provide functional modules for a radio communication terminal.

Background

The first commercially attractive cellular telephones or terminals were introduced in the market at the end of the 1980's. Since then, a lot of effort has been made in making smaller terminals, with much help from the miniaturisation of electronic components and the development of more efficient batteries. Today, numerous manufacturers offer pocket-sized terminals with a wide variety of capabilities and services, such as packet-oriented transmission and multiple radio band coverage.

In order to attract customers the terminal manufacturers have therefore taken further measures to strengthen their position in the competition, one such being to offer terminals with detachable covers or housings. If a user wishes to change the outer appearance of his communication terminal, he can simply buy a new cover of the desired kind. The old cover is preferably released by a simple grip without the aid of tools, where after the new cover can be snapped on. A detachable cover is generally a fairly simple element, essentially formed from a single piece of plastic or possibly metal. The cover may represent only the front side of the terminal, i.e. the side of the terminal carrying the user interface generally comprising a terminal display and keypad, a microphone and a loudspeaker. In such a design, the cover forms a separate part of the housing of the terminal, or optionally an auxiliary part to be attached outside the housing. Alternatively, the cover may include more than one piece, e.g. a front piece and a back piece devised to substantially enclose the terminal. The detachable covers are often provided in different colours, and also with more advanced patterns such as logos or images.

The detachable covers of the prior art mainly create an aesthetic effect, changing the visual appearance of the terminal. They do not, however, have any effect on the functions of the terminal. Other solutions for creating this aesthetic effect, without having to change the cover, have also been proposed.

EP 1079584 by Laurikka et al discloses a cover for an electronic device, such as a communication terminal, whose colour can be changed by means of a control signal. That cover is advantageously produced by using a material, which changes

its colour as a result of the effect of an electric or electromagnetic control signal. Such a material is for example electronic ink, with which a conventional cover is coated. The appearance of cover can hence be controlled by a signal from the communication terminal. When a call or a text message arrives in the
5 communication terminal, it indicates this to the user by changing the colour of the cover.

Also EP 564127 by Blonder shows an apparatus housing capable of changing colour. The housing has a transparent outer layer, covering a layer of electrically switchable light modulating material. This invention too suggests indicating e.g. a
10 telephone ring by changing the housing colour.

Today there is a market need for a variety of radio communication terminals with different features in different price ranges. However, more different terminal varieties leads to increased costs in development, production, stock, distribution, and marketing. Furthermore, there is a constant or even increasing pace in
15 development of new components, such as electronics, batteries, and displays, rendering the lifetime of a terminal model shorter and shorter before the next model is introduced. Today terminals are sold with different features and at different prices. Such features include e.g. touch-screen, speakerphone, special buttons etc. Normally, the only thing that can be changed for the user is the appearance of the
20 housing, and the software controlling ring signals and displayed images.

Summary of the invention

A problem with portable communication terminals of today is that it is expensive to produce a wide variety of different phones in order to attract a large
25 market. Furthermore, some features or parts of the terminals develop faster than other features, which means that one outdated part might decrease the market value for the entire terminal, even if it is otherwise fully competitive. An object of the present invention is therefore to provide a solution for making portable communication terminals suit a wider range of customers, and more easily
30 adaptable to various functions.

According to a first aspect, this object is fulfilled by a radio communication terminal comprising data processing means for controlling terminal functions, and attaching means for releasable attachment of a housing to the terminal, wherein said terminal comprises a multipath connector connected to the data processing means,
35 said multipath connector including a terminal system connector, and a housing connector for communicative connection of an attached housing to the data processing means.

Preferably, the multipath connector is positioned such that the system connector is accessible from the outside of the terminal, and such that said housing

connector faces a front or rear side of the terminal. In one embodiment said housing connector faces a different direction than the system connector.

Preferably, the multipath connector is positioned at an end of the terminal, such that the system connector is accessible in a longitudinal direction of the terminal, whereas said housing connector faces a front or rear side of the terminal. The multipath connector may comprise two housing connectors, for communicative connection of a front housing and a rear housing.

Advantageously, said multipath connector comprises connector poles that are branched to said system connector and said housing connector.

According to a second aspect, the object of the invention is fulfilled by a disconnectable housing for a radio communication terminal according to what has been outlined above, comprising attaching means for releasable attachment of the housing to the terminal. Said housing comprises a terminal connector devised to provide bus connectivity with said terminal upon attachment, and functional means connected to said terminal connector for affecting the function of an attached terminal.

Preferably, said functional means for affecting the function of an attached terminal comprises a micro controller. Furthermore, said functional means for affecting the function of an attached terminal preferably comprises a functional member, adding a feature to the terminal when the housing is attached thereto. Alternatively, said functional means for affecting the function of an attached terminal comprises a functional member, devised to modify a feature of the terminal when the housing is attached thereto.

In one embodiment said functional member comprises a touch-sensitive display.

In one embodiment said functional member comprises a speaker for hands free operation.

In one embodiment said functional member comprises a digital image recorder.

According to a third aspect, the object of the invention is fulfilled by a radio communication terminal and housing combination, wherein cooperating attaching means are devised for releasable connection of the housing to the terminal, and wherein said housing comprises means for affecting the function of the terminal, and where cooperating housing-to-terminal connector means are provided for communicative connection between the terminal and an attached housing.

Preferably, said radio communication terminal and housing combination comprises a radio communication terminal and a housing according to any of the embodiments and examples given above.

According to a fourth aspect, the object of the invention is fulfilled by a multipath connector for a radio communication terminal, which multipath connector has two separate connector interfaces comprising interconnected poles. Preferably, the multipath connector includes connection pads for connection to a terminal PCB.

- 5 In one embodiment, the multipath connector is devised to be fixed to an end of a terminal PCB, such that one connector interface faces outwardly in the longitudinal direction of said PCB, and a second connector interface faces outwardly substantially perpendicular to the PCB. In a variant of that embodiment, the multipath connector has a third connector interface facing outwardly
- 10 substantially perpendicular to the PCB in the opposite direction from said second connector interface.

The detailed description shows specific features of various embodiments related to the aspects above.

15 Brief description of the drawings

The features and advantages of the present invention will be more apparent from the following description of the preferred embodiments with reference to the accompanying drawings, on which

- Fig. 1 schematically illustrates a communication terminal as seen from the front, in accordance with an embodiment of the invention;
- 20 Fig. 2 illustrates the terminal of Fig. 1 in a sectional side view;

Fig. 3 schematically shows the terminal of Fig. 2 and two active housings that are connectable to the terminal;

- Fig. 4 illustrates a terminal when assembled with the two active housings of
- 25 Fig. 3;

Fig. 5 schematically illustrates a terminal connector including both the terminal system connector and housing connectors;

Fig. 6 further illustrates a version of the connector of Fig. 5, wherein the system connector is branched to provide connection also to active housings;

- 30 Figs 7A – 11 illustrate various embodiments of active housings and their attachment to a terminal.

Detailed description of preferred embodiments

- The present description relates to the field of radio communication terminals.
- 35 The term radio terminal or communication terminal, also denoted terminal in short in this disclosure, includes all mobile equipment devised for radio communication with a radio station, which radio station also may be mobile terminal or e.g. a stationary base station. Consequently, the term radio terminal includes mobile telephones, pagers, communicators, electronic organisers, smartphones, PDA:s

(Personal Digital Assistants) and DECT terminals (Digital Enhanced Cordless Telephony). Hence, although the structure and characteristics of the antenna design according to the invention is mainly described herein, by way of example, in the implementation in a mobile phone, this is not to be interpreted as excluding the implementation of the inventive antenna design in other types of radio terminals, such as those listed above. Furthermore, it should be emphasised that the term comprising or comprises, when used in this description and in the appended claims to indicate included features, elements or steps, is in no way to be interpreted as excluding the presence of other features elements or steps than those expressly stated.

Exemplary embodiments will now be described with references made to the accompanying drawings.

According to the invention, a terminal is provided with front and rear housings, i.e. shells or covers, that are active. By active is here meant that the housings can include electronics that together with the phone provides additional and/or modified features. For this purpose, the terminal is provided with a housing connector, connectable to a co-operating terminal connector on the releasable housing. Furthermore, means for attaching and securing the housings to the terminal are also included, devised in a co-operating manner, though not shown in all the drawings. The attaching means may be arranged in any suitable shape, several of which are well known to the skilled person and used today. The housings may e.g. be snapped on and maintained in place by a spring force, or be screwed on. The specific manner is not crucial for the present invention.

Fig. 1 illustrates a radio communication terminal 1, in the form of a cellular phone. Terminal 1 is carried in a chassis 16, directly or indirectly supporting the other components of the terminal. Terminal 1 is devised with a user-input interface, in the displayed embodiment comprising a microphone 14 and a keypad 19. The user input interface may also or comprise a touch-sensitive display in addition to or instead of the keypad 19. Furthermore, a user output interface of the terminal 1 comprises a loudspeaker 15 and a display 18. All of these features are well known in the prior art. Though not shown in Fig. 1, the communication terminal 1 further includes an antenna, radio transmission and reception electronics, and a power supply in the form of a battery. Communication terminal 1 is also devised with a computer system, including a microprocessor with associated memory and software. In order to co-operate and communicate with a releasable active housing, the terminal 1 is further devised with a connector 17.

Fig. 2 illustrates the terminal 1 in a sectional view from its left side, as seen in Fig. 1. In this drawing, the different operative parts of the terminal are schematically shown, including those shown in Fig. 1. The chassis 16 is indicated

by the dashed line, and its specific shape is not relevant. A printed circuit board PCB 10 carries the electronics 11 of the terminal, preferably including data processing means such as a micro processor system, or the like, with associated memory. An antenna 13 is further included, the particular type of which is irrelevant to the invention. Typical antenna types include micro strip antennas, Planar Inverted-F Antennas PIFA, and stub antennas. A battery 12 is included to feed the electronics with electrical energy.

Fig. 3 illustrates the terminal 1 and two releasable housings, a back housing 20 and a front housing 30. The arrows in Fig. 3 indicate that housings 20 and 30 are attachable to terminal 1. The illustration of the terminal 1 in Fig. 3 further includes attaching means 27 in the purely exemplary shape of recesses formed in the sides of the terminal. Furthermore, the active housings 20, 30 are provided with protruding members 26 and 36, respectively, devised to latch into engagement with the corresponding recesses 27 in the terminal 1. It should be noted that the present invention is not restricted to having both an active housing attached to the rear and the front of terminal 1. On the contrary, these two active housings 20, 30 are preferably, but need not be, independent of each other, separately communicating with the terminal 1. Therefore, only one of the housings 20, 30 may be attached, the drawing indicating both simply to show this possibility too. The specific character of the active housings 20, 30 is not shown in Fig. 2, but different examples are given below and in the subsequent drawings. Each housing 20, 30 has a shell part 21, 31, forming part of the exterior housing of the assembled terminal 1 when attached thereto. The shell part also carries, directly or indirectly, the other members of the respective active housing. Each active housing 20, 30 further includes a terminal connector 24, 34. Preferably, the terminal connectors 24, 34 and the cooperating housing connector on the terminal offer a full system bus connectivity. Each active housings 20, 30 also comprises a micro controller 25, 35 communicatively connected to the housing connector 24, 34. A functional member 22, 32, adding to or modifying the features of the terminal 1 may also be included, connected to and controlled by the micro controller 25, 35. The micro controller 25, 35 preferably has a dedicated software stored therein, for the purpose of controlling the interaction with the terminal. The active housing may have its own power supply in the form of a small battery or capacitor, but preferably makes use of the terminal battery 12 through the terminal connector 24, 34. In one embodiment, yet another releasable cover may be attached onto a first attached cover, thereby providing a further function to the terminal. For this purpose the covers 20, 30 may also include cover connectors 23, 33.

Fig. 4 illustrates the assembled terminal 40, comprising terminal 1 and the attached housings 20, 30, but without the separate parts of the terminal 1 and the

active housings 20, 30 indicated. As before, the assembled terminal may also comprise the terminal 1 and only one active housing 20 or 30. Furthermore, there may be more than two active housings, attached beside or over each other. When the active housings 20, 30 are connected to the terminal 1 they may fully enclose the terminal 1, but they may also occupy only parts of the exterior of the terminal 1.

Fig. 5 illustrates the connector 17 and a cut-off portion of the PCB 10 to which it is connected. The connector 17 comprises a number of connecting elements or poles preferably made from a suitable metal, such as copper, carried in an insulating support structure of e.g. plastic. In a preferred embodiment, connector 17 includes, on one side, the system connector of the terminal 1. In Fig. 5 the system connector 50 is arranged on the bottom side of the terminal 1, which is a common approach in radio communication terminals of today. The system connector 50 is accessible from the outside of the terminal 1, and comprises a set of poles that for instance are usable for connecting the terminal to a battery charger without having to dismantle the battery 12 from the terminal 1. Furthermore, the system connector 50 includes poles for data communication with the terminal 1, which e.g. can be used for attaching auxiliary components to the terminal 1, such as audio or video players or recorders, extra keypads, and so on. The poles indicated in the drawing are merely exemplary, and the invention is in no way restricted to the shown shape and layout of the poles.

The connector 17 also includes one or more housing connectors 51, 52 and 53, for connecting to active housings, each comprising a set of one or several electric poles. Consequently, the connector 17 is a multipath connector. Preferably, the housing connector 52 is identical to the opposite housing connector 51. According to the displayed embodiment of Fig. 5, the connector 17 consequently carries both the system connector 50 and the housing connectors 51, 52, 53. The sideways facing connector 53 need not be included.

Fig. 6 further illustrates a more specific version of the embodiment of Fig. 5. Herein, a piece of the connector 17 is cut out, such that one connector pole 60 is laid open. From Fig. 6 it is evident that this embodiment includes poles 60, which are included in both the system connector 50 and in one or more housing connectors 51, 52. The pole 60 includes a conductive member with contact parts 61, 62, 63 which are accessible from different sides. The connector pole 60 is connected to the PCB 10, e.g. by a solder pad 64.

Consequently, the system connector 50 as it is hitherto known is modified such that it comprises connector faces also to the releasable active housings. Therefore, the active housings make use of the same electrical interface as is defined by the system connector 50. The housing connectors 51, 52 may have one

or more poles in common with the system connector, but preferably all, although all of them need not be used by the attached active housing.

It should be noted that the system connector 50 need not necessarily face outwardly in the longitudinal direction of the terminal, as is illustrated in Figs 5 and 6. Instead, it may face outwardly from e.g. the rear of the terminal, i.e. being substantially parallel to the rear housing connector 52. The active housings could in such an embodiment merely be devised not to cover the system connector 50.

Figs 7A to 11 illustrate in a schematic manner some different embodiments of active housings to a terminal 1. These rather simple drawings indicate the co-operating housing and terminal connectors, and the member providing the optional feature, included in the active housing.

Fig. 7A illustrates a side view of a front housing 70 carrying a large touch-sensitive display 71, which housing 70 is connectable to terminal 1. Fig. 7B illustrates the assembled terminal 72 from the front, clearly showing the display 71. A stylus 72 can be used to input data to the terminal 1, 72 through the display 71.

Fig. 8A illustrates a side view of a front housing 80 carrying an enlarged speaker 81 for hands free functionality, which housing 80 is connectable to terminal 1. Fig. 8B illustrates the assembled terminal 82 from the front, showing the hands free speaker 81. In the displayed embodiment the speaker 81 adds to the length of the terminal. Optionally, the speaker may be arranged to be positioned such that it instead adds to the height, i.e. thickness of the terminal. A different speakerphone arrangement is illustrated in Fig. 11, described below.

Fig. 9B illustrates a side view of a rear housing 90 carrying a digital image recorder 91, which housing 90 is connectable to terminal 1. Fig. 9A illustrates the assembled terminal 92 from the rear, indicating a lens of the digital image recorder 91. Fig. 9C illustrates the assembled terminal 92 from the front, where only the terminal 1 itself is visible since no front active housing has been attached. The digital image recorder may be a snapshot camera and/or a video recorder.

Fig. 10A illustrates a side view of a rear housing 100, carrying an auxiliary remote control 101, which housing 100 is connectable to terminal 1. Fig. 10B illustrates the assembled terminal 102 from the front, showing the face of terminal 1. The remote control sender, and possibly receiver, 101 is also indicated even though it may not be visible from the front. Such a remote control 101 may e.g. comprise an infrared transmitter, or a bluetooth chip.

Fig. 11 illustrates a rather different embodiment of a releasable active housing 110, although it relates to the embodiment of Figs 8A and 8B. First of all, this drawing illustrates another way of attaching the terminal 1 to the housing 110, more or less by sliding the terminal 1 into the housing 110 as indicated by the arrow. The active housing 110 is in this embodiment devised to provide conference

telephone capabilities to a portable terminal 1. The active housing 110 may be devised to rest on a desktop or the like, and has a bottom rest surface for this purpose, facing downwards in the drawing. In alternative embodiments the active housing may of course be devised with the rest surface such that the terminal is
5 maintained in a different position, such as straight up or at a tilted angle. The active housing 110 of Fig. 11 is shaped to receive the terminal 1 in a horizontal arrangement, as indicated in the drawing, where a side view of the terminal 1 is given. The active housing 110 has an enlarged speaker 111, or at least a more powerful speaker 111 than the ordinary terminal speaker, and the speaker 111 is
10 therefore selected to be suitable for conveying sound to a wider audience than just one user holding the terminal to the ear. Preferably, the terminal 1 is placed in the active housing 110 with the front of the terminal 1 facing upwards, such that the terminal display and keypad can be conveniently used. The conference telephone active housing 110 may also be devised with suitable conference phone controls
15 112. Such controls include volume control and a secrecy function, such that the terminal is set to a listen only mode. The conference phone controls 112 preferably comprise buttons, the triggering of which is relayed to the terminal through the co-operating connectors of the housing 110 and the terminal 1.

The embodiments described above in conjunction with the drawings
20 represent examples of how active housings according to the invention may be devised. However, many other examples are possible, a few of which are outlined here without reference to any specific drawing.

A front housing could be include a user input interface adapted to suit a certain category of users, such as children or elderly people. Such an active housing
25 can have only a few large buttons with custom images and/or text, like "Nurse", "Daughter", "Taxi", "Mum", "Dad", "Home", "Work" etc. Preferably the logic contained in the software for the housing micro controller is also devised to set up the terminal 1 in a special way upon attachment. For instance, the housing software may be triggered by the attachment of the active housing to the terminal to reject all
30 incoming messages, only allow incoming calls from certain numbers, and so on.

In one embodiment the active housing may be adapted for playing games on the terminal, having dedicated gaming buttons and an analog joystick.

An active housing may also include particular alarm functions for indicating incoming calls or messages, by illuminating the shell of the cover.

35 Some terminals include a calculator function. However, it is generally quite simple, and in one embodiment an active housing may include a more advanced calculator with buttons for more complex operations, such as logarithmic calculation and integration.

One embodiment of an active housing includes a Memory Stick reader, and can thus provide an increased memory for the terminal.

The active housing may be a media player, such as an FM radio, or a digital music player capable of retrieving audio either from a carrier or from a software
5 memory. Today such digitally stored audio systems include the Mini Disc system and the MP3 format, but the future will of course provide other alternatives.

In one embodiment the active housing is adapted to interact with a further component. For instance, an active housing may be devised to interact with a cordless headset through a suitable channel, such as by IR or radio, e.g. bluetooth.
10 This way the terminal can easily be adapted to be able to cooperate with such a cordless headset even though that feature was not included when the terminal was purchased. The headset could even be packaged and sold together with the active housing. Such an active housing may also include a holder for the headset, and or a charger for the headset, such that the headset may be charged by either a special
15 battery or capacitor in the active housing, or by the battery of the terminal.

The principles of the present invention have been described in the foregoing by examples of embodiments or modes of operations. However, the invention should not be construed as being limited to the particular embodiments discussed above. A skilled person would realise that the accommodation of an active housing
20 with full system bus connectivity to the terminal having a multipath connector gives rise to many further advantages or possibilities than those listed in the instant specification. Thus, the above described embodiment should be regarded as illustrative rather than restrictive, and it should be appreciated that variations may be made in those embodiments by persons skilled in the art, without departing from
25 the scope of the present invention as defined by the appended claims.

CLAIMS

1. A radio communication terminal (1) comprising data processing means for controlling terminal functions, and attaching means (27) for releasable attachment
5 of a housing (30) to the terminal, **characterised in** that said terminal comprises a multipath connector (17) connected to the data processing means, wherein said multipath connector includes a terminal system connector, and a housing connector for communicative connection of an attached housing to the data processing means.
- 10 2. The radio communication terminal as recited in claim 1, **characterised in** that the multipath connector is positioned such that the system connector is accessible from the outside of the terminal, and such that said housing connector faces a front or rear side of the terminal.
- 15 3. The radio communication terminal as recited in claim 1, **characterised in** that the multipath connector is positioned such that the system connector is accessible from the outside of the terminal, and such that said housing connector faces a different direction than the system connector.
- 20 4. The radio communication terminal as recited in any of the previous claims, **characterised in** that the multipath connector is positioned at an end of the terminal, such that the system connector is accessible in a longitudinal direction of the terminal, and where said housing connector faces a front or rear side of the terminal.
- 25 5. The radio communication terminal as recited in any of the previous claims, **characterised in** that the multipath connector comprises two housing connectors, for communicative connection of a front housing and a rear housing.
- 30 6. The radio communication terminal as recited in any of the previous claims, **characterised in** that said multipath connector comprises connector poles that are branched to said system connector and said housing connector.
- 35 7. Disconnectable housing (30) for a radio communication terminal according to any of the previous claims 1 - 6, comprising attaching means (36) for releasable attachment of the housing to the terminal, **characterised in** that said housing comprises a terminal connector (34) devised to provide bus connectivity with said terminal upon attachment, and functional means (32,35) connected to said terminal connector for affecting the function of an attached terminal (1).

8. The disconnectable housing as recited in claim 7, **characterised in** that said functional means for affecting the function of an attached terminal comprises a micro controller (35).

5

9. The disconnectable housing as recited in claim 7 or 8, **characterised in** that said functional means for affecting the function of an attached terminal comprises a functional member, adding a feature to the terminal when the housing is attached thereto.

10

10. The disconnectable housing as recited in claim 7 or 8, **characterised in** that said functional means for affecting the function of an attached terminal comprises a functional member, devised to modify a feature of the terminal when the housing is attached thereto.

15

11. The disconnectable housing as recited in claim 9, **characterised in** that said functional member comprises a touch-sensitive display (71).

12. The disconnectable housing as recited in claim 9, **characterised in** that said functional member comprises a speaker (81,111) for hands free operation.

20

13. The disconnectable housing as recited in claim 9, **characterised in** that said functional member comprises a digital image recorder (91).

14. A radio communication terminal and housing combination, wherein cooperating attaching means are devised for releasable connection of the housing to the terminal, **characterised in** that said housing comprises means for affecting the function of the terminal, and where cooperating housing-to-terminal connector means are provided for communicative connection between the terminal and an attached housing.

30

15. The radio communication terminal and housing combination as recited in claim 14, **characterised in** that it comprises a radio communication terminal according to any of the previous claims 1 to 6 and a housing according to any of the previous claims 7 to 13.

35

16. A multipath connector (17) for a radio communication terminal (1), **characterised in** that the multipath connector has two separate connector interfaces (50, 51) comprising interconnected poles (60).

17. The multipath connector as recited in claim 16, **characterised in** that it includes connection pads for connection to a terminal PCB (10).

- 5 18. The multipath connector as recited in claim 17, **characterised in** that it is devised to be fixed to an end of a terminal PCB, such that one connector interface (50) faces outwardly in the longitudinal direction of said PCB, and a second connector interface (51) faces outwardly substantially perpendicular to the PCB.
- 10 19. The multipath connector as recited in claim 18, **characterised in** that a third connector interface (52) faces outwardly substantially perpendicular to the PCB in the opposite direction from said second connector interface.

THIS PAGE BLANK (USPTO)

1/5





FIG. 1

THIS PAGE BLANK C/S TO



2/5










DT12 Rec'd PGT/PTO 12 JAN 2005

THIS PAGE BLANK (11/11/04)

3/5



THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)

5/5




FIG. 10A




FIG. 10B

80
~




FIG. 11

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 03/05715

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04M1/02 H04M1/725 H01R12/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04M H01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 608 899 A (MITSUBISHI ELECTRIC CORP) 3 August 1994 (1994-08-03) abstract column 4, line 17 -column 5, line 14 column 6, line 1 - line 49 figures 6,7,10,11,14-17	1-6
X	WO 02 41607 A (SENDO INTERNAT LTD ;ROPER MICHAEL JOHN (GB)) 23 May 2002 (2002-05-23) abstract page 1, line 29 -page 3, line 5 page 5, line 26 -page 7, line 10 figures 1,2	7-10,14, 15
Y		11-13
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

15 October 2003

Date of mailing of the international search report

24/10/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bianchi, D

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/05715

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 01 37229 A (KEASHLY DUSTY ; POMERLEAU DANIEL GUY (CA); WILDCARD COMM CANADA INC) 25 May 2001 (2001-05-25) page 16, line 15 - page 17, line 8 page 19, line 26 - page 20, line 17 figures 2A-2K, 4A, 4B, 4E, 4F	11, 13
Y	US 5 655 017 A (FISHMAN DAVID A) 5 August 1997 (1997-08-05) column 3, line 11 - line 26 figure 1	12
X	GB 2 339 342 A (NEC TECHNOLOGIES) 19 January 2000 (2000-01-19) abstract page 5, line 10 - line 22 page 7, line 1 - line 7 figures 2-4, 8	16-18
Y	EP 0 518 578 A (YAMAICHI ELECTRIC MFG) 16 December 1992 (1992-12-16) column 4, line 3 - line 16 figures 1-3	19
Y	EP 0 518 578 A (YAMAICHI ELECTRIC MFG) 16 December 1992 (1992-12-16) column 4, line 3 - line 16 figures 1-3	19
P, X	US 6 424 842 B1 (WINSTEAD RUSSELL) 23 July 2002 (2002-07-23) abstract column 3, line 14 - line 50 column 5, line 9 - line 19 figures 2-8	16
A	EP 0 760 541 A (NOKIA MOBILE PHONES LTD ; HIROSE ELECTRIC CO LTD (JP)) 5 March 1997 (1997-03-05) abstract column 2, line 17 - line 30 column 3, line 5 - line 15 figure 1	16-18
A	GB 2 362 071 A (NOKIA MOBILE PHONES LTD) 7 November 2001 (2001-11-07) abstract page 1, line 17 - page 2, line 6 page 4, line 6 - page 5, line 10 page 6, line 13 - page 7, line 6 figures 1, 2	7, 14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/05715

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0608899	A	03-08-1994	JP 2833397 B2 09-12-1998
			JP 6232779 A 19-08-1994
			DE 69428613 D1 22-11-2001
			DE 69428613 T2 18-07-2002
			EP 0608899 A2 03-08-1994
			US 5487099 A 23-01-1996
			US 5490202 A 06-02-1996
WO 0241607	A	23-05-2002	WO 0241607 A1 23-05-2002
			AU 2387502 A 27-05-2002
WO 0137229	A	25-05-2001	CA 2289884 A1 18-05-2001
			AU 1683701 A 30-05-2001
			BR 0015766 A 06-08-2002
			WO 0137229 A1 25-05-2001
			CA 2391387 A1 25-05-2001
			CN 1423802 T 11-06-2003
			EP 1230625 A1 14-08-2002
			JP 2003515304 T 22-04-2003
US 5655017	A	05-08-1997	NONE
GB 2339342	A	19-01-2000	NONE
EP 0518578	A	16-12-1992	JP 4368792 A 21-12-1992
			CA 2070692 A1 15-12-1992
			DE 69205627 D1 30-11-1995
			EP 0518578 A1 16-12-1992
US 6424842	B1	23-07-2002	NONE
EP 0760541	A	05-03-1997	JP 9063716 A 07-03-1997
			EP 0760541 A2 05-03-1997
			US 5812660 A 22-09-1998
GB 2362071	A	07-11-2001	AU 6591801 A 20-11-2001
			BR 0110368 A 18-02-2003
			CA 2407917 A1 15-11-2001
			CN 1428037 T 02-07-2003
			WO 0186922 A1 15-11-2001
			EP 1282973 A1 12-02-2003
			US 2002030103 A1 14-03-2002
			US 2002037738 A1 28-03-2002

THIS PAGE BLANK (USPTO)